





# EVINRUDE Johnson



ENGLISH

### Power Trim/Tilt Hydraulic Assembly P/N 434804

#### Preface

This manifold assembly contains pressure relief components that were not used in some early models. Refer to CU model parts book for earlier models. Follow installation and test procedures in CD/CU model *Service Manual* - Trim/Tilt Section for earlier models.

The installation of this kit involves procedures described in detail in the **Service Manual** for your product. If you do not have the required literature and do not wish to purchase it, have this kit installed by your Dealer.

Refer to the Service Manual for your product for information on disassembly, reassembly, testing, and other procedures required to complete the installation of this part.

#### Installation

**1 2** This manifold has counterbored mounting holes **A** that require the longer screw **B**, with an extended shank, to fit in the counterbore as shown. Discard old screws. New screws (included) marked 17-4 **C** must be used.

FRANÇAIS

### Assemblage hydraulique d'angle d'assiette/relevage assistés P/N 434804

#### Préface

Cet assemblage de collecteur comprend des éléments de détente de pression qui n'étaient pas utilisés sur certains modèles antérieurs. Référez-vous au livre de pièces du modèle CU quand il est question de modèles antérieurs. Suivez les procédés d'installation et d'essai du *Manuel d'entretien* de modèle CD/CU - Section angle d'assiette/relevage pour les modèles antérieurs.

L'installation de ce kit implique les procédés décrits en détail dans le **Manuel d'entretien** concernant votre produit. Si vous ne possédez pas la publication nécessaire et vous ne désirez pas en faire l'achat, faites installer ce kit par votre concessionnaire.

Référez-vous au manuel d'entretien de votre produit pour vous munir des informations de démontage, de remontage, d'essais et d'autres procédés requis pour accomplir l'installation de cette pièce.

#### Installation

**1 2** Ce collecteur est muni de trous épaulés **A** qui nécessitent une vis plus longue **B**, ayant une tige allongée, afin de s'ajuster dans l'épaulement de la manière indiquée. Jetez les vieilles vis. Les nouvelles vis (comprises) marquées 17-4 **C** doivent être utilisées.