

GEAR SET BREAK-IN PERIOD

This gear set, as does all gear sets, REQUIRES a BREAK-IN PERIOD. We recommend that these instructions be attached to the final user's copy of your repair order.

INSTRUCTIONS FOR 10 HOUR BREAK-IN PERIOD

- 1. Avoid full throttle starts.
- 2. DO NOT operate at constant speeds for extended periods.
- 3. DO NOT exceed 75% of full throttle during the first 5 hours of operation. During the next 5 hours, full throttle operation is permissible for brief periods.
- 4. Shift into forward gear a minimum of 10 times during break-in, with moderated engine speed after each shift.

N-1585

GEAR SET BREAK-IN PERIOD

This gear set, as does all gear sets, REQUIRES a BREAK-IN PERIOD. We recommend that these instructions be attached to the final user's copy of your repair order.

INSTRUCTIONS FOR 10 HOUR BREAK-IN PERIOD

- 1. Avoid full throttle starts.
- 2. DO NOT operate at constant speeds for extended periods.
- 3. DO NOT exceed 75% of full throttle during the first 5 hours of operation. During the next 5 hours, full throttle operation is permissible for brief periods.
- 4. Shift into forward gear a minimum of 10 times during break-in, with moderated engine speed after each shift.