



NFB™ SAFE-T® II MECHANICAL ROTARY STEERING SYSTEM:

Major OEMs use Teleflex Safe-T II, and so will your customers. It's the next generation of Safe-T, the world's #1 rotary steering system — rugged, compact, lightweight, and with Teleflex No FeedBack technology. This ultra-smooth 3-turn system takes the work out of steering most V-4 outboard powered boats. The Safe-T II helm is a drop-in replacement for current generation Safe-T QC with no dash modifications!

APPLICATIONS:

NFB Safe-T II single-cable systems are suitable for most single-station boats with a single non-power-assisted outboard engine up to V-4 and minimal engine flutter or steering instability. Safe-T II accepts wheels up to 16" diameter. (NFB Safe-T II is available in single cable configuration only). Replaces nearly all standard Safe-T® steering without dash modifications.

FEATURES:

- Patented No FeedBack™ Steering mechanism.
- Quick response of 3 turns lock-to-lock.
- Minimal clutch free play.
- Standard 3/4" round tapered steering shaft.
- Stainless steel cable output ends.
- Fast, easy installation: uses Teleflex Quick Connect (QC) cable.
- Kits include: cable, helm, 90° bezel and hardware.
- Meets A.B.Y.C. standards.
- Meets N.M.M.A. certification requirements.

COMPLETE SYSTEM	
NFB Safe-T II Steering Kit	SS132XX
COMPONENTS	
NFB Safe-T II Helm	SH5150P
QC Cable	SSC62XX
Rotary NFB Bezel (90°)	SB27150P
OPTIONS	
NFB Safe-T II Tilt Dash Module	SHT91190
Each Kit Includes Tilt Helm & Tilt Mechanism	
NFB Safe-T II Tilt Helm	SH91190P*
Sport Tilt Mechanism	SH91800P
Sport Plus Tilt Mechanism	SH91900P
Bezel (20°)	SB27483P
Cable Gard (fits most tilt tubes)	SA39329P
SERVICE ITEMS	
QC II Cable (for most Teleflex rotary) (Includes SA27620P Helm Converter)	SSC61XX
Steering Wheel Hardware Kit (Old #2745417P)	SA27454P
Spent Travel Tube (Rotary NFB)	SA38603P
Hitch Pin for Quick Connect Helms (Old #2727514P)	SA27245P
* Requires tilt mechanism to complete Tilt Steering system installation.	

