

COMPLETE SYSTEM	
Safe-T QC Steering Kit (single cable)	SS137XX
COMPONENTS	
Safe-T QC Single Helm	SH5094P
QC Cable	SSC62XX
Safe-T QC Bezel (90°)	SB27484P
OPTIONS	
Safe-T QC Sgl. Tilt Dash Module Each Kit Includes Tilt Helm & Tilt Mechanism	SHT91523
Sport Tilt Mechanism	SH91800P
Sport Plus Tilt Mechanism	SH91900P
Safe-T QC Single Tilt Helm	SH91523P*
Safe-T QC Bezel (20°)	SB27483P
Cable Gard (fits most tilt tubes)	SA39329P
SERVICE ITEMS	
QC II Cable (For most Teleflex rotary helms) Includes SA27620P Helm Converter	SSC61XX
QC II Threaded Helm Converter (in SSC61 cable)	SA27620P
Steering Wheel Hardware Kit (Old #2745417P)	SA27454P
Spent Travel Tube	SA35680P
Hitch Pin for Quick Connect Helms (Old #2724514P)	SA27245P
Safe-T "TS" Helm (Old Style)	SH5023P
Safe-T QC Dual Helm	SH5294P†
Safe-T QC Dual Tilt Helm	SH91524P*†

- * Requires tilt mechanism to complete Tilt Steering system installation. † For dual cable. If steering is NOT power-assisted, upgrading to NFB
- 4.2 Dual Cable is recommended.

SAFE-T® QC MECHANICAL ROTARY STEERING SYSTEM:

Traditional Teleflex Marine mechanical steering is still the choice for sterndrives, inboards and other power assisted applications.

It's just right for power steered boats in which No FeedBack™ systems are not required.

Safe-T® QC offers the quick response of three-turn steering, and easy installation with a patented, notools-required cable connection at the helm.

APPLICATIONS:

Virtually all power-assisted sterndrive boats with wheels up to 16" diameter. Safe-T QC® replaces all Teleflex Safe-T helms made since 1968 with little or no dash modifications. (Requires use of SSC62 QC or SSC61 QC II steering cable.)

For single station use only. Safe-T QC accepts wheels up to 16" diameter.

Components are available for dual cable systems, but we recommend No-FeedBack steering for all dual cable steered, non-power-assisted outboards and sterndrives. See the NFB 4.2 Dual Cable and SeaStar PRO sections of this catalog.

FEATURES:

- Quick-response of 3 turns lock-to-lock.
- Kits include: cable, helm, 90° bezel and hardware.
- Standard 3/4" round tapered steering shaft.
- Stainless steel cable output ends.
- Fast, easy installation: uses simple snap-in cable connection, Teleflex Quick Connect (QC) cable, and industry-standard Safe-T mounting hardware.
- Meets A.B.Y.C. standards.
- Meets N.M.M.A. certification requirements.

<u>DISCLAIMER</u>: This system is only recommended as replacement for the original system as installed by the boat manufacturer. Teleflex always recommends NFB helms for outboard applications. NFB helms lock out steering loads caused by propeller torque eliminating the driver fatigue normally experienced with a standard helm. Patented Teleflex steering helms are a drop in replacement for Safe-T systems.

