

SNAPP. The fuel filter change that changes everything.

SNAPP is big protection for small engines with fuel flows up to 40 gph and makes every filter change literally a snap. Fast, easy, clean. No tools are needed – when it’s time for service, simply snap in a new filter. Simple installation and a patented priming system mean that protecting your engine investment is now ... a SNAPP.



Fast, easy, clean, SNAPP is a fuel filter change for the better.

The world turns to Racor for filtration solutions that provide ultimate protection from water and solid contamination. This is filtration that includes two innovations often copied but never quite duplicated – the powerful protection of patented, world-class Aquabloc® filter media and, the Racor trademark, a clear bowl that allows for at-a-glance inspection of fuel system integrity.



Quick-release squeeze tabs make filter changes a snap.

Permanent mounting bracket is stainless steel for withstanding corrosive environments.

SNAPP is a one-piece fuel filter water separator for 24/7 protection .

Heavy-duty high-impact nylon construction won't ever rust or corrode, even in humid conditions.

Clear bowl for at-a-glance inspection.

The rugged clear bowl allows on-the-spot inspection for water in fuel – a significant advantage when troubleshooting fuel quality.

The Racor self-venting drain means easy service with no mess – twist, drain, done.

Legendary Aquabloc® filter media in 2, 10 or 30 micron rating.

The Aquabloc® media is the world's definitive filtration protection – it's 99% effective in separating water and solid contamination from marine and diesel fuels.



Part #	Description	Specifications
23281-02	Fuel Filter with Bracket - 2 Micron	2 micron - 40 gph (151 lph)
23281-10	Fuel Filter with Bracket - 10 Micron	10 micron - 34 gph (129 lph)
23281-30	Fuel Filter with Bracket - 30 Micron	30 micron - 26 gph (100 lph)
R23280-02	Fuel Filter - Service - 2 Micron	Aquabloc Micron Rating
R23280-10	Fuel Filter - Service - 10 Micron	2, 10, or 30 micron
R23280-30	Fuel Filter - Service - 30 Micron	Height
23299-02	Fuel Filter with Bracket - with Drain - 2 Micron	7.8" (198 mm)
23299-10	Fuel Filter with Bracket - with Drain - 10 Micron	Width
23299-30	Fuel Filter with Bracket - with Drain - 30 Micron	3.8" (97 mm) at bracket
R23298-02	Fuel Filter - Service - with Drain - 2 Micron	Depth
R23298-10	Fuel Filter - Service - with Drain - 10 Micron	4.1" (104 mm)
R23298-30	Fuel Filter - Service - with Drain - 30 Micron	Water Sump Capacity
		3.4 oz. (100 ml)
		Bracket Material
		Stainless Steel
		Port Size
		3/8" (9.5 mm)
		Quick-Connect Fittings
		3/8" (9.5 mm) (per SAE J2044)
		Rated Pressure
		50 PSI (3.5 bar)
		Water Removal Efficiency
		99%
		Rated Temperature Range
		-20° to 150°F (-29° to 66°C)
Part #	SNAPP Fittings	
RK23319	90° Quick-Connect Fitting Kit, 3/8" x 3/8"	
RK23320	Straight Quick-Connect Fitting Kit, 3/8" x 5/16"	
RK23321	90° Quick-Connect Fitting Kit, 3/8" x 5/16"	